



## TECHNICAL SPECIFICATION

### ENVIROLAY 28

---

#### Roll Dimensions

Length (M)	Width (M)	Area (Sq.M)
11	1.37	15.07

---

Thickness	Weight	BS 5808	BS 4790
mm +/- 10%	g/m2 +/- 10%	Classification	Flammability
7	950	GD/U	Pass – Low Radius

---

Carbon Footprint per roll	BS 4745	BS EN ISO 140-8:1998
345g of co2/kg of product	Thermal Insulation	Impact Sound Reduction
4930g	2.42 Tog	-

---

Comfort/Durability	Recommendations
6/10	Bedrooms * Living ✓ Hall, Stairs & Landing ✓

---

#### Installation

Subfloors should be dry, clean and free of oil, grease & damp.

Fitting should meet the British Standard code of practice BS 5325 & be undertaken by experienced fitters.

---

✓ Suitable

\* Highly Recommended

[www.envirolay.co.uk](http://www.envirolay.co.uk)



---

*Please note: This document does not constitute a manufacturing specification. It details important technical performance and physical characteristics of the product only. Please contact the Technical Department for any further information.*

Texfelt Ltd

South Lane Mills, South Lane, Elland, West Yorkshire HX5 0HQ. UK

Telephone +44 (0) 1422 376791 Facsimile +44 (0) 1422 376810

Email [sales@textfelt.co.uk](mailto:sales@textfelt.co.uk) Website [www.textfelt.co.uk](http://www.textfelt.co.uk)