



TECHNICAL SPECIFICATION

ENVIROLAY 48

Roll Dimensions				
Length (M)	Width (M)	Area (Sq.M)		
11	1.37	15.07		
Thickness				
mm +/- 10%	Weight	BS 5808	BS 4790	
12	g/m2 +/- 10%	Classification	Flammability	
	1640	HC/U	Pass – Low Radius	
Carbon Footprint per roll				
345g of co2/kg of product		BS 4745	BS EN ISO 140-8:1998	
8450g		Thermal Insulation	Impact Sound Reduction	
		3.35 Tog	34dB	
Comfort/Durability				
Recommendations		Heavy Floor, Wheel traffic & Castor Chairs		
9/10	Bedrooms	Living	Hall, Stairs & Landing	
	✓	*	*	*

Installation

Subfloors should be dry, clean and free of oil, grease & damp.

Fitting should meet the British Standard code of practice BS 5325 & be undertaken by experienced fitters.

✓ Suitable

* Highly Recommended

www.envirolay.co.uk



Please note: This document does not constitute a manufacturing specification. It details important technical performance and physical characteristics of the product only. Please contact the Technical Department for any further information.

Texfelt Ltd

South Lane Mills, South Lane, Elland, West Yorkshire HX5 0HQ. UK

Telephone +44 (0) 1422 376791 Facsimile +44 (0) 1422 376810

Email sales@textfelt.co.uk Website www.textfelt.co.uk