



TECHNICAL SPECIFICATION

ENVIROLAY 54

Roll Dimensions

Length (M)	Width (M)	Area (Sq.M)
11	1.37	15.07

Thickness mm +/- 10%	Weight g/m ² +/- 10%	BS 5808 Classification	BS 4790 Flammability
14	1831	HC/U	Pass – Low Radius

Carbon Footprint per roll 345g of co ₂ /kg of product 9505g	BS 4745 Thermal Insulation 3.42 Tog	BS EN ISO 140-8:1998 Impact Sound Reduction 35 dB
--	---	---

BS EN 20354:1993/ISO 354:1985 – TP14

Acoustic Performance, Practical Absorption Coefficient

250	500	1000	2000	4000
0.25	0.7	0.95	0.9	0.8

Comfort/Durability	Recommendations			Heavy Floor, Wheel traffic & Castor Chairs
10/10	Bedrooms ✓	Living *	Hall, Stairs & Landing *	*

Installation

Subfloors should be dry, clean and free of oil, grease & damp.

Fitting should meet the British Standard code of practice BS 5325 & be undertaken by experienced fitters.

✓ Suitable

* Highly Recommended

www.envirolay.co.uk



Please note: This document does not constitute a manufacturing specification. It details important technical performance and physical characteristics of the product only. Please contact the Technical Department for any further information.

Texfelt Ltd

South Lane Mills, South Lane, Elland, West Yorkshire HX5 0HQ. UK

Telephone +44 (0) 1422 376791 Facsimile +44 (0) 1422 376810

Email sales@textfelt.co.uk Website www.textfelt.co.uk