

Roll Dimension

Length (m)	Width	Area (m ²)
11	1.37	15.07

Thickness

mm +/- 10%
7

Weight

g/m² +/- 10%
950

BS 5808

Classification
GD/U

BS 4790

Flammability
Pass - Low Radius

Carbon Footprint per roll

345g of CO₂/kg of product
4930g

BS 4745

Thermal Insulation
2.42 Tog

BS EN ISO 140-8 : 1998

Impact Sound Reduction
33dB

BS EN 20354:1993 / ISO 354:1985 - TP14

Acoustic Performance, Practical Absorption Coefficient

250	500	1000	2000	4000
0.25	0.5	0.85	0.9	0.8

BS EN ISO 10580:2012

VOC Tested
None Detected

BS EN 14184 Pt1

Formaldehyde Tested
None Detected

Comfort / Durability

Recommendations

6/10	*	Living	Hall	Heavy Floor
		Bedrooms	Stairs	Wheel Traffic
		✓	Landing	Castor Chairs
			✓	

Installation

Subfloors should be dry, clean and free of oil, grease & damp.

Fitting should meet the British Standard code of practice BS 5325 & be undertaken by experienced fitters

- ✓ Suitable
- * Highly Recommended



www.envirolay.co.uk

Please note: This document does not constitute a manufacturing specification. It details important technical performance and physical characteristics of the product only. Please contact the Technical Department for any further information.

Telephone +44 (0) 1274 905411

Facsimilie +44 (0) 1274 905412

Email sales@textfelt.co.uk

Website www.textfelt.co.uk