

**Roll Dimension**

Length (m)	Width	Area (m <sup>2</sup> )
11	1.37	15.07

Thickness	Weight	BS 5808	BS 4790
mm +/- 10%	g/m <sup>2</sup> +/- 10%	Classification	Flammability
13	1831	HC/U	Pass - Low Radius

Carbon Footprint per roll	BS 4745	BS EN ISO 140-8 : 1998
345g of CO <sub>2</sub> /kg of product	Thermal Insulation	Impact Sound Reduction
9505g	3.42 Tog	35db

**BS EN 20354:1993 / ISO 354:1985 - TP14**

Acoustic Performance, Practical Absorption Coefficient

250	500	1000	2000	4000
0.25	0.7	0.95	0.9	0.8

BS EN ISO 10580:2012	BS EN 14184 Pt1
VOC Tested	Formaldehyde Tested
None Detected	None Detected

Comfort / Durability	Recommendations																
10/10	<table border="0"> <tr> <td>Bedrooms</td> <td>Living</td> <td>Hall</td> <td>Heavy Floor</td> </tr> <tr> <td>*</td> <td>*</td> <td>Stairs</td> <td>Wheel Traffic</td> </tr> <tr> <td></td> <td></td> <td>Landing</td> <td>Castor Chairs</td> </tr> <tr> <td></td> <td></td> <td>*</td> <td>*</td> </tr> </table>	Bedrooms	Living	Hall	Heavy Floor	*	*	Stairs	Wheel Traffic			Landing	Castor Chairs			*	*
Bedrooms	Living	Hall	Heavy Floor														
*	*	Stairs	Wheel Traffic														
		Landing	Castor Chairs														
		*	*														

**Installation**

Subfloors should be dry, clean and free of oil, grease & damp.

Fitting should meet the British Standard code of practice BS 5325 & be undertaken by experienced fitters

- ✓ Suitable
- \* Highly Recommended



[www.envirolay.co.uk](http://www.envirolay.co.uk)

Please note: This document does not constitute a manufacturing specification. It details important technical performance and physical characteristics of the product only. Please contact the Technical Department for any further information.

Telephone +44 (0) 1274 905411

Facsimilie +44 (0) 1274 905412

Email [sales@textfelt.co.uk](mailto:sales@textfelt.co.uk)

Website [www.textfelt.co.uk](http://www.textfelt.co.uk)