

Roll Dimension

Length (m)	Width	Area (m ²)
11	1.37	15.07

Thickness	Weight	BS 5808	BS 4790
mm +/- 10%	g/m ² +/- 10%	Classification	Flammability
12	1640	HC/U	Pass - Low Radius

Carbon Footprint per roll	BS 4745	BS EN ISO 140-8 : 1998
345g of CO ² /kg of product	Thermal Insulation	Impact Sound Reduction
8450g	3.35 Tog	34dB

BS EN 20354:1993 / ISO 354:1985 - TP14

Acoustic Performance, Practical Absorption Coefficient

250	500	1000	2000	4000
0.25	0.65	1	0.9	0.85

BS EN ISO 10580:2012	BS EN 14184 Pt1
VOC Tested	Formaldehyde Tested
None Detected	None Detected

Comfort / Durability	Recommendations	Living	Hall	Heavy Floor
	Bedrooms		Stairs	Wheel Traffic
			Landing	Castor Chairs
9/10	*	*	*	*

Installation

Subfloors should be dry, clean and free of oil, grease & damp.

Fitting should meet the British Standard code of practice BS 5325 & be undertaken by experienced fitters

- ✓ Suitable
- * Highly Recommended



www.envirolay.co.uk

Please note: This document does not constitute a manufacturing specification. It details important technical performance and physical characteristics of the product only. Please contact the Technical Department for any further information.

Telephone +44 (0) 1274 905411

Facsimilie +44 (0) 1274 905412

Email sales@textfelt.co.uk

Website www.textfelt.co.uk