

## TECHNICAL SPECIFICATION

### HEART N SOUL

#### Roll Dimension

Length (m)	Width	Area (m <sup>2</sup> )
7.3	1.37	10

Thickness	Weight	BS 5808	BS 4790
mm +/- 10%	g/m <sup>2</sup> +/- 10%	Classification	Flammability
10.5	2445	L/U	Pass - Low Radius

BS 4745
Thermal Insulation
2.48 Tog

Comfort / Durability	Recommendations	Living	Hall	Heavy Floor
10/10	Bedrooms		Stairs	Wheel Traffic
	*	*	Landing	Castor Chairs
			*	*

#### Installation

Subfloors should be dry, clean and free of oil, grease & damp.

Fitting should meet the British Standard code of practice BS 5325 & be undertaken by experienced fitters

- ✓ Suitable
- \* Highly Recommended



[www.envirolay.co.uk](http://www.envirolay.co.uk)

*Please note: This document does not constitute a manufacturing specification. It details important technical performance and physical characteristics of the product only. Please contact the Technical Department for any further information.*

#### Texfelt Ltd

Unit 2 Cutler Heights Business Park, Cutler Heights Lane, Bradford, West Yorkshire BD4 9AW. UK

Telephone +44 (0) 1274 905411

Facsimilie +44 (0) 1274 905412

Email [sales@textfelt.co.uk](mailto:sales@textfelt.co.uk)

Website [www.textfelt.co.uk](http://www.textfelt.co.uk)