

TECHNICAL SPECIFICATION:

ROLL DIMENSIONS:

THICKNESSES AVAILABLE	LENGTH	WIDTH	AREA	WEIGHT g/m ²	ROLL WEIGHT kg	DENSITY kg/m ³
8mm	10m	1.5m	15m ²	750g/m ²	11.25kg	93kg/m ³

TESTING DATA:

STANDARD	DESCRIPTION	SPRINGBOND 8mm
BS 4790	Flammability	Pass – Low Radius
BS 5808: 1991(2011)	Underlays & Textile Floor Coverings	General Domestic GD/U
BS 2576:1986	Breaking Strength & Elongation	Elongation at 30N – 1.38% Breaking Strength 228 N
BS 4939:1987 (2003)	Static Loading	Thickness Loss After 24 hrs Recovery 31%
BS 4052:1987	Dynamic Loading Test	Thickness Loss After 1000 Impacts 22%
BS 4098:1975 (2003)	Work Of Compression Test	Mean Work Of Compression Retained 57%
BS5808 Appendix A:1991(2011)	Resistance to Breaking & Cracking – Degree of Cracking	None
BS 4745	Thermal Insulation	2.2 Tog
BS 1902-5.8(1992)	Thermal Conductivity	0.0349W/M2K
ISO140	Impact Sound Reduction	37 db Indicative
TVOC	TVOC after 3 days	PASS (46.6 µg/m ³ – extremely low)*
Sustainability	Fully recyclable at end of serviceable life	YES

* Maximum permitted levels of TVOC to obtain a PASS = 8260 µg/m³

USAGE:

	COMFORT	DURABILITY	AREA RECOMMENDATIONS (★ – HIGHLY RECOMMENDED)			
			BEDROOMS	LIVING ROOMS	HALL, LANDINGS, STAIRS, CORRIDORS	HEAVY FLOOR, WHEEL TRAFFIC & CASTOR CHAIRS
9mm	8/10	7/10	★	★	★	

INSTALLATION:

Subfloors should be dry, clean and free of oil, grease & damp.

Fitting should meet the British Standard code of practise BS5325 & be undertaken by experienced fitters.



BRITISH MADE



FLAME RESISTANT



COMFORT & SUPPORT



NOISE REDUCING



CHEMICAL FREE



EASY FIT



ECO-FRIENDLY



THERMAL INSULATION



SAFE – NO HARMFUL VOCs



BREATHABLE



85% RECYCLED CONTENT



100% RECYCLABLE